

CB-S24 - 2S2M - 2W - 4R - P - R - STD - 4 X 5 - 0 - 0 0 0 0 0

2 - Pipe
4 - Pipe

S - Single Circuit SC

2 - 1/2" Connection Pipe

M - Male NPT Fittings
N - No Fittings Straight Pipe

Length Inlet Diameter

2FT 4"
4FT 5"
6FT 6"
8FT 8"

(STD, TG1, TG2, EXP) - Border Style

T - Top Handing
R - Right Handing
L - Left Handing

P - Perforated Grille

Induction Ratio 2:1, 3:1, 4:1, 6:1
(2R, 3R, 4R, 6R) - Nozzle Type

2W - 2 Way Throw

0 - Galvanized Plenum
P - Painted Plenum

0 - Fixed Hanging Bracket

0 - Standard Round Inlet

0 - Standard No Insulation
E - External Insulation

0 - Self Finish Coil
F - Flat Black Coil

0 - RAL9010 30% Gloss
RX - Special Color

Sample Codes:

CB-S24-2W-2S2M-2R-P-T-STD-4X6-0-00000
 CB-S24-2W-4S2M-6R-P-R-TG1-6X8-RX-0000P
 CB-S24-2W-4S2M-4R-P-L-TG2-8X5-0-0E000
 CB-S24-2W-2S2M-3R-P-R-EXP-8X8-0-FE00P